



Product Fiche

Supplier name	Arada
Product Code	LAGOM-CERAMIC-S2
Energy Efficiency Class (wood)	A
Direct Heat Output (wood)	4.1 Kw
Indirect Heat Output (wood)	N/A
Energy Efficiency Index (wood)	104.27
The useful energy efficiency at nominal heat output and at minimum load (wood)	79.9 %

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations.
Appliance will become very hot during use.

Dimensions

Width	528 mm
Height	996 mm
Depth	398 mm
Flue Diameter	149 mm
Depth from back to centre of top flue	199 mm
Axis height of rear flue	863 mm
Ideal log length / diameter	250 mm / 100 mm

Performance

	Wood Fuel
Energy Efficiency Class	A
Nett Efficiency	79.9 %
Nominal Output	4.1 kW
Mean CO Emission (@13% O ₂)	0.09%
DIN+ particulate	23 Nmg/m ³
Mean NOx Emission (@13% O ₂)	90 Nmg/m ³
Mean OGC Emission (@13% O ₂)	83 Nmg/m ³
Flue Gas Mass Flow	3.7 g/s
Flue Gas Temperature	269 °C
Average wood consumption	1.25 kg/hour

This stove is produced under licence by our EU partner.

Features

Stove body type	Freestanding
Ecodesign Ready	Yes
Approved for smoke control areas	No
Integrated heat shield	Yes
Suitable for direct air connection	Yes
Suitable for non-combustible 12mm hearth	Yes
Weight nett (unpacked weight)	150 Kg

Minimum distance to combustibles

	Single Walled Flue	Single Walled Flue– Corner
Rear	150 mm	300 mm
Side	200 mm	250 mm
Top	800 mm	
	Twin Walled Flue	Twin Walled Flue– Alcove
Rear	100 mm	
Side	200 mm	
Top	800 mm	

Direct air spigot location

When viewing the rear side of stove

Spigot diameter	125 mm
Spigot orientation	Vertical
Height from floor	311 mm
Axis distance from rear	82 mm
Lateral position	Centre